

# ARTURO EPOXY ACCELERATOR

## PRODUCT DESCRIPTION:

Arturo Epoxy Accelerator is a solvent free accelerator for Arturo Epoxy Primers/Scratch Coats.

## AREA OF APPLICATION\*\*\*

Excellent for the use of new-build projects, repair and renovation.

During the mixing process, the Arturo Epoxy Accelerator can be added to the following Arturo Epoxy Primers/Scratch Coats:

- ▶ Arturo EP6200 Scratch Coat
- ▶ Arturo EP6500 Primer
- ▶ Arturo EP6955 Primer OS8
- ▶ Arturo EP2500 (only as scratch coat)

## PRODUCT FEATURES/BENEFITS

- ▶ It shortens the curing time to 80%\*
- ▶ Universally applicable for Arturo EP Primers/Scratch Coats
- ▶ Re-apply the second layer after approx. 3-4 hours\*
- ▶ Short decommissioning of the room
- ▶ To be added to Arturo Epoxy Primers/Scratch Coats that are in stock
- ▶ Install the primer, scratch coating and screed in one day\*
- ▶ Easy to process thanks to its low viscosity



## PRODUCT DATA

Verpakkingsgrootte	0,7 kg / 25 kg
Houdbaarheid	Minstens 12 maanden
Kleur	Transparant

## TECHNICAL SPECIFICATIONS:

Mengverhouding	7% op een gemengde set
Beloopbaar	EP6955: ca. 3 uur EP6200/EP6500: ca. 2 uur
Overlaagbaar	EP6955: ca. 4 uur EP6200/EP6500: ca. 3 uur

## DISCLAIMER

The information on this product sheet concerning the processing and application of this product is based on our experience with the product under standard conditions and with correct product storage and use. In practice, differences between equipment, subfloors and working conditions mean that no guarantee for a specific work result nor any liability, arising out of any legal relationship whatsoever, can be inferred either from the information on this data sheet or from any verbal advice given, unless caused by intent or gross negligence on our part. In this case the user must demonstrate that he has promptly forwarded to us in writing all necessary information for proper and effective evaluation of the circumstances. Users must test the products to check whether they are suitable for the intended application. We reserve the right to amend the information on technical data sheets. The intellectual property rights of third parties must be heeded. The most recent technical data sheet always applies. This can be requested from us or downloaded from [www.arturoflooring.com](http://www.arturoflooring.com). Our general terms and conditions of sale and delivery also apply.

## PROTECTION OF THE WORKPLACE AND ENVIRONMENT:

The use of barrier cream is recommended. When mixing wear a protective dust-mask. Refer to the notes on protection of the workplace and the environment in the Product Information Sheets for the other installation materials used.

## DISPOSAL:

Where possible, collect product residues and re-use. Do not empty into drains, sewers or ground. Empty, scraped containers are recyclable.

\* At 20°C, 65% relative humidity.

\*\* Avoid large temperature fluctuations and differences, this can lead to a temperature shock which has a negative influence on the final result.

\*\*\* For recreation rooms systems with AgBB certification must be used.